KNC



2 7/32" [56.1mm]





Mill Finish

STD

ОРТ

Standard

Optional

Bronze Anodized

Black Anodized

Clear Anodized

Screw Options

Screw Type: **G** 3/16" X 1-3/4" Hi-Lo Tapping Thread, Grey Phillips Drive, Concrete Screws (5/32" Pre-Drill Required)



#10 X 1-3/4" Stainless Steel Flat Head, Robertson Drive, Type A Screws (Complete With Nylon Anchor)



#10 X 2" Stainless Steel Flat Head, Tamper-Resistant Torx Drive, Type A Screws (Complete With Nylon Anchor)

Features • Mill Finish Extruded Aluminum with Silicone Application • Ideal for Residential Commercial & Industrial	Operation	Stop Strip
Application Ideal for Residential Commercial & Industrial	Features	Mill Finish Extruded Aluminum with Silicone
	Application	Ideal for Residential, Commercial & Industrial

Customer Name:

Job No./Name:

1/2"

[12.7mm]

4

Date:

Provided By:

Notes:

KN Crowder

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3 T. 1–866–999–1562 customerservice@kncrowder.com © 2020-2022 K.N. Crowder Mfg. Inc. All Rights Reserved.