



FEATURES

- 600 lbs. [272 kg] weight capacity
- Delrin wheels and precision ball bearings provide smooth and quiet door operation
- Cycle tested for up to 150,000 cycles without fail
- ADA Compliant (Barrier-free) design
- Also available in stainless steel (CFT-201-SS)

COMPLETE 1 DOOR KIT BREAKDOWN



**1 - CFT-200-BP Flat Track**  
x length based on kit size (e.g. 72 in [1829 mm] kit for 36 in [914 mm] wide door)



**CFT-211-WB-BP Wall Mount Brackets**  
quantity dependent on track length  
complete with 5/16-18 flat head socket lag screws and expansion shields



**CFT-201-BP Top Mount Hangers**  
complete with anti-lift and custom mounting screws  
**2 hangers** for doors up to 300 lbs. [136 kg]  
**3 hangers** for doors up to 450 lbs. [204 kg]  
**4 hangers** for doors up to 600 lbs. [272 kg]



**2 - CFT-210-BP Shock Absorbing Stops**  
clamp around flat track



**1 - C-914 Aluminum Guide Channel**  
x length based on kit size (e.g. 36 in [914 mm] guide channel for 72 in [1829 mm] kit)  
**1 - C-913 Floor Guide**  
complete with screws

OPTIONAL

Door Locks & Pulls



Notes:

- Door thickness
- Baseboard/trim thickness, if applicable


Customer Name	Job No./Name	Date	Provided By

Notes


# CFT-201-BP



## COMPLETE ELEVATION VIEW



## PRODUCT DIMENSIONS



Installation  
Instructions



Customer Name	Job No./Name	Date	Provided By

Notes