

CRT-102-214-BP



FEATURES

- 600 lbs. [272 kg] weight capacity
- Delrin wheels and precision ball bearings provide smooth and quiet door operation
- Adjustable in-track stops
- Cycle tested for up to 150,000 cycles without fail
- ADA Compliant (Barrier-free) design
- Also available in stainless steel (CRT-102-214-SS)
- For 2 1/4 in [57.2 mm] - 2 1/2 in [63.5 mm] thick door

COMPLETE 1 DOOR KIT BREAKDOWN



1 - CRT-100-BP Round Track
x length based on kit size (e.g. 72 in [1829 mm] kit for 36 in [914 mm] wide door)



CRT-122-WB-BP Wall Mount Brackets
quantity dependent on track length
complete with 5/16-18 flat head socket lag screws and expansion shields



CRT-102-214-BP Strap Mount Hangers
complete with anti-lift and custom mounting screws
2 hangers for doors up to 350 lbs. [159 kg]
3 hangers for doors up to 450 lbs. [204 kg]
4 hangers for doors up to 600 lbs. [272 kg]



2 - CRT-120-BP Shock Absorbing Stops
clamp around flat track



1 - C-914 Aluminum Guide Channel
x length based on kit size (e.g. 36 in [914 mm] guide channel for 72 in [1829 mm] kit)
1 - C-913 Floor Guide
complete with screws

OPTIONAL

Door Locks & Pulls



Notes:

Door thickness

Baseboard/trim thickness, if applicable

Customer Name	Job No./Name	Date	Provided By
<hr/>	<hr/>	<hr/>	<hr/>

Notes

KNC

Diagram illustrating the track system components and dimensions:

- track length**: Indicated by a dimension line at the top.
- 2x CRT-120 Stops**: Located at the left end of the track.
- 2x CRT-102-214 Hangers**: Located at the left end of the track, mounted on the wall.
- 1 1/2 in [38.1 mm]**: Dimension for the distance between the hanger bolts.
- see right**: Reference to the right side of the page.
- minimum 5 1/4 in [133.4 mm] to center of hanger bolt**: Dimension for the distance from the wall to the center of the hanger bolt.
- CRT-100 Track**: The main track component.
- CRT-122-WB Wall Brackets c/w CRFT-WBS Wall Bracket Spacers**: Located at the right end of the track.
- C-914 Guide Channel with C-913 Floor Guide**: Located at the bottom of the track.
- recommended door overlap: 2 in [50.8 mm]**: Dimension for the overlap of the door.
- door width**: Indicated by a dimension line at the bottom.

Technical drawing of the CR-122-WB wall bracket assembly, showing dimensions and components. The drawing includes a side view of the assembly mounted on a wall and a cross-section view of the door and bracket.

Dimensions:

- 1 3/8 in [34.9 mm]
- 3/4 in [19.1 mm]
- 9 3/4 in [247.7 mm]
- 3 in [76.2 mm]
- 3 1/8 in [79.2 mm]
- 2 1/4 in [57.2 mm]
- 3 in [76.2 mm]
- 3/4 in [19.1 mm]
- 10 3/4 in [273.1 mm]
- 5/8 in [15.9 mm] gap back of door to wall (based on 2 1/4 in [57.2 mm] thick door)
- 1 1/8 in [34.9 mm] minimum
- 1 5/8 in [41.3 mm] maximum
- 1/8 in [3.2 mm]
- 3/8 in [9.5 mm]
- door thickness minimum
- 2 1/4 in [57.2 mm] maximum
- 2 1/2 in [63.5 mm]
- 1 in [25.4 mm]
- 29/32 in [23.0 mm]

Components:

- CR-122-WB Wall Brackets
- CRFT-WBS Wall Bracket Spacer
- CRT-AL2 Anti-Lift
- Ø3 1/2 in [88.9 mm] wheel
- Ø1 in [25.4 mm] Round Track
- Guide Clearance Min - Max: 5/16 - 5/8 in [7.9 - 15.9 mm]

**Provided By**

KN Crowder

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3
T. 1-866-999-1562 customerservice@kncrowder.com kncrowder.com
© 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.