

## CT-20/5



**Operation:** Stair Nosing

**Features:** Mill Finish Extruded Aluminum with Lanel Insert (P.V.C.)

**Application:** Ideal for Residential, Commercial & Industrial

**Maximum Length:** 156 in [3962 mm]

**Customer Name**

**Job No./Name**

**Date**

**Provided By:**

**Notes**

**KN Crowder**

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3  
 T. 1-866-999-1562 [customerservice@kncrowder.com](mailto:customerservice@kncrowder.com) [kncrowder.com](http://kncrowder.com)  
 © 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.

## FINISHES


Mill Finish

Special \_\_\_\_\_

OPT STD

Standard


Optional




## SCREW OPTIONS



Screw Type: G  
 3/16" X 1-3/4" Hi-Lo Tapping Thread,  
 Grey Phillips/Robertson Combo Drive,  
 Concrete Screws  
 (5/32" pre-drill required)



Screw Type: H  
 #10 X 1-3/4" Stainless Steel Flat Head,  
 Robertson Drive, Type A Screws  
 (complete with nylon anchor)



Screw Type: I  
 #10 X 2" Stainless Steel Flat  
 Head, Tamper-Resistant Torx  
 Drive, Type A Screws  
 (complete with nylon anchor)