

## CT-22/138



**Operation:** Stair Nosing

**Features:** Mill Finish Extruded Aluminum with Lanel Insert (P.V.C.)

**Application:** Ideal for Residential, Commercial & Industrial

**Maximum Length:** 156 in [3962 mm]




## FINISHES

Mill Finish


Special \_\_\_\_\_

OPT STD


## SCREW OPTIONS



**Standard**  
Screw Type: G  
3/16" X 1-3/4" Hi-Lo Tapping Thread,  
Grey Phillips/Robertson Combo Drive,  
Concrete Screws  
(5/32" pre-drill required)



**Optional**  
Screw Type: H  
#10 X 1-3/4" Stainless Steel Flat Head,  
Robertson Drive, Type A Screws  
(complete with nylon anchor)



Screw Type: I  
#10 X 2" Stainless Steel Flat  
Head, Tamper-Resistant Torx  
Drive, Type A Screws  
(complete with nylon anchor)

Customer Name \_\_\_\_\_

Job No./Name \_\_\_\_\_

Date \_\_\_\_\_

Provided By: \_\_\_\_\_

Notes \_\_\_\_\_

**KN Crowder**

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3  
T. 1-866-999-1562 [customerservice@kncrowder.com](mailto:customerservice@kncrowder.com) [kncrowder.com](http://kncrowder.com)  
© 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.