

CT-706



Operation: Threshold

Features: Mill Finish Extruded Aluminum

Application: Ideal for Residential, Commercial & Industrial

Maximum Length: 156 in [3962 mm]

Customer Name

Job No./Name

Date

Provided By:

Notes

KN Crowder

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3
 T. 1-866-999-1562 customerservice@kncrowder.com kncrowder.com
 © 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.

FINISHES

STD

Mill Finish

Bronze Anodized


Black Anodized

Clear Anodized

Special _____


OPT

Standard




Screw Type: G
 3/16" X 1-3/4" Hi-Lo Tapping Thread,
 Grey Phillips/Robertson Combo Drive,
 Concrete Screws
 (5/32" pre-drill required)

Optional



Screw Type: H
 #10 X 1-3/4" Stainless Steel Flat Head,
 Robertson Drive, Type A Screws
 (complete with nylon anchor)



Screw Type: I
 #10 X 2" Stainless Steel Flat
 Head, Tamper-Resistant Torx
 Drive, Type A Screws
 (complete with nylon anchor)

STD

Mill Finish

Bronze Anodized

Black Anodized

Clear Anodized

Special _____

SCREW OPTIONS