

CT-708 NEW



KNC



OPTSTD

FINISHES

- Mill Finish
- Special _____


Standard

SCREW OPTIONS

 Screw Type: G
 3/16" X 1-3/4" Hi-Lo Tapping Thread, Grey
 Phillips/Robertson Combo Drive, Concrete Screws
 (5/32" pre-drill required)

Optional

 Screw Type: H
 #10 X 1-3/4" Stainless Steel Flat Head, Robertson
 Drive, Type A Screws
 (complete with nylon anchor)

 Screw Type: I
 #10 X 2" Stainless Steel Flat Head,
 Tamper-Resistant Torx Drive, Type A Screws
 (complete with nylon anchor)

Operation: Threshold
Features: Mill Finish Extruded Aluminum
Application: Ideal for Residential, Commercial & Industrial
Maximum Length: 156 in [3962 mm]

| | | | |
|---------------|--------------|------|-------------|
| Customer Name | Job No./Name | Date | Provided By |
|---------------|--------------|------|-------------|

Notes

KN Crowder

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3
 T. 1-866-999-1562 customerservice@kncrowder.com kncrowder.com
 © 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.