

CT-709

NEW




## FINISHES

Mill Finish

Special \_\_\_\_\_


OPT STD




## SCREW OPTIONS



Screw Type: G  
 3/16" X 1-3/4" Hi-Lo Tapping Thread, Grey  
 Phillips/Robertson Combo Drive, Concrete Screws  
 (5/32" pre-drill required)



Screw Type: H  
 #10 X 1-3/4" Stainless Steel Flat Head, Robertson  
 Drive, Type A Screws  
 (complete with nylon anchor)



Screw Type: I  
 #10 X 2" Stainless Steel Flat Head,  
 Tamper-Resistant Torx Drive, Type A Screws  
 (complete with nylon anchor)

**Operation:** Threshold**Features:** Mill Finish Extruded Aluminum**Application:** Ideal for Residential, Commercial & Industrial**Maximum Length:** 156 in [3962 mm]**Customer Name****Job No./Name****Date****Provided By****Notes**

KN Crowder

1220 Burloak Drive, Burlington, Ontario, Canada, L7L 6B3  
 T. 1-866-999-1562 [customerservice@kncrowder.com](mailto:customerservice@kncrowder.com) [kncrowder.com](http://kncrowder.com)  
 © 2020-2025 K.N. Crowder Mfg. Inc. All Rights Reserved.