



# CROWDERFRAME POCKET DOOR KITS



**New!**  
**TYPE C-2X6**  
 For 2X6 Wall Construction  
 Up to 150 lbs. [68 kg] per door



**Improved!**  
**TYPE C**  
 For 2X4 Wall Construction  
 Up to 150 lbs. [68 kg] per door

Our Type C Crowderframe Pocket Door Kit now comes in a 2X6 version. This complete kit specifically engineered for 2X6 wall construction, eliminates the need for shim kits, making installation fast and easy. For a quick and easy install, we chose our C-411 Quick Release Hangers for these pocket door kits. Check out the drawings above to see how easily the door connects and adjusts! Our nylon wheels with precision ball bearings ensure smooth and quiet door operation.



**Improved!**  
**TYPE B**  
 For 2X4 Wall Construction  
 Up to 125 lbs. [57 kg] per door



Our C-400 hangers combined with nylon wheels with precision ball bearings ensure smooth and quiet door operation.

Additional features for all kits above:

- Complete with roll formed steel uprights for less deflection and easy to screw into for drywall fastening.
- Choose to install the door before OR after the drywall goes up.
- Adjust door height and plumb while the door is up.
- Faster and easier installation than a traditional pocket built on-site.
- For single or bi-parting door applications.

### How to Specify/Order:

Type C-W-2X6 Crowderframe Pocket Door Kit (ideal for 1-3/4" [44.5 mm] doors in 2X6 wall construction)

Type C-W Crowderframe Pocket Door Kit (ideal for 1-3/4" [44.5 mm] doors in 2X4 wall construction)

Available for doors from 18" [457 mm] to 48" [1219 mm] wide x 80" [2032 mm] to 120" [3048 mm] high, please provide door size when specifying/ordering.

Type B-B Crowderframe Pocket Door Kit (ideal for 1-3/8" [34.9 mm] doors)

Available for doors from 18" [457 mm] to 36" [914 mm] wide x 80" [2032 mm] to 96" [2438 mm] high, please provide door size when specifying/ordering.